



Honda RC-51 / VTR-1000 SP1 - Installation Instructions

(slip on system)

Thank you for selecting and purchasing a TiForce exhaust system for your Honda RC-51 / VTR-1000 SP1. TiForce is the world's finest titanium exhaust system available today. Please install your new system as explained in the following pages, and in accordance with given precautions. Instructions are also available in Adobe Acrobat PDF format on the TiForce website (www.TiForce.com).

Before Installation:

- Verify that all parts and accessories have been included (see list below).
- Coat all exhaust pipe mating joints with anti-seize compound / lubricant (Finish Line Ti-Prep packet included).
- Read and review these instructions, cautions, diagrams and images prior to starting any work.

-
1. Remove the lower fairing.
 2. Remove the existing exhaust system from the mid pipes rearward. Save the exhaust clamps for reuse. Save the stock exhaust can mounting bolts and nut for the end can to the passenger footpegs for reuse as well.
 3. Inspect the original exhaust gaskets. Replace as necessary.
 4. Slide the tail pipes into place. Do not tighten the clamps at this point.
 5. Slide the TiForce end cans into place.
 6. Loosely attach the two rubber bands, stainless steel bands K, and stay / hanger G to each end can using the supplied 6mm hardware H. See figure 1 for details.
 7. Using the stock provided mounting point on the passenger footpeg, and using the stock mounting bolt, mount the end can loosely, allowing for some adjustment. Insert the stock mounting bolt through the stay / hanger G (see figure 1).
 8. Attach the supplied springs to all the joints (from the tail pipes to the TiForce end cans).
 9. Make sure the exhaust system is free and clear, if necessary jiggle the system to adjust for proper clearance.
 10. Carefully align the two stainless bands K so that they are parallel to each other, and spaced properly on the can, then tighten the 6mm hardware H and the stock mounting bolt hardware. Make sure that the rubber pads fully cover the band(s). **USE CAUTION WHEN TIGHTENING THE 6MM HARDWARE AND THE TWO BANDS SO AS NOT TO CRUSH OR DISTORT THE SLEEVE OF THE CAN(s).**
 11. Go back and tighten the two exhaust clamps per factory specification.
 12. Using some brake and contact cleaner on a clean rag, carefully wipe down the entire exhaust system to remove any residual oils, anti seize, fingerprints and dirt prior to starting the motor. **FAILURE TO CLEAN THE TUBING AND CAN MAY RESULT IN PERMANENT STAINING OF THE SYSTEM WHEN HEATED.**
 13. Check that all hardware is properly tightened, then start the motor and check for exhaust leaks.
 14. Reinstall the fairing and tighten any fasteners per factory specification.

*Please note that Figure 1 lists quantities of hardware necessary per TiForce end can installation. With the RC-51 / VTR-1000 model, the quantities are twice what is listed (please see the parts list below).



General Cautions For Exhaust System Installations:

- **CAUTION** - For your safety, carefully read these instructions and those above, and fully familiarize yourself with the content before beginning installation and use. Keep these instructions in a safe place for future reference. Install the exhaust system as explained in these instructions.
- **DANGER** – when the motor is running, and shortly after it has been turned off, the motorcycle, the exhaust system and end-can will be hot. Severe burns, bodily injury and even death may result.
- **DANGER** - Keep gasoline and other flammable materials away from the exhaust system at all times. Exposure of gasoline and to heat can lead to fire.
- **CAUTION** - Stop the motorcycle should the exhaust system come in contact with people or animals. Never touch the exhaust system when hot. Direct contact with the system can cause burns.
- **DANGER** - Allow the motor to cool before installing or removing the exhaust system. Working with a hot motor can lead to burns.
- **CAUTION** - Stand the motorcycle on a flat and level surface and ensure that the motorcycle is stable before installing the exhaust system. Bodily injury and / or death could result to you or others if the motorcycle falls over. Damage may also result to the motorcycle or nearby property or equipment.
- **DANGER** - Start and run the motorcycle in a well-ventilated area. With prolonged exposure to exhaust gas you run the risk of severe oxygen deficiencies, bodily injury or death may result.
- **CAUTION** – Install the muffler only on the specified model of motorcycle. Improper installation will lead to loss of performance and or damage to the motorcycle.
- **CAUTION** – Do not disassemble, modify or remodel this exhaust system.

TiForce high performance exhaust systems are distributed exclusively by Orient Express Powersports. Please have your dealer contact Orient Express for technical assistance, information, and parts if needed.

TiForce / Orient Express
81 Hanse Ave
Freeport, NY 11520

800.645.6521
516.546.5232 tel
516.546.5247 fax

www.orientexpress.com
www.tiforce.com
sales@tiforce.com

PARTS LIST (Honda CBR-929rr)

- Exhaust pipe R – 1x
- Exhaust pipe L – 1x
- End can R – 1x
- End can L – 1x
- M8 Washer – 2x
- End can stay / hanger G – 2x
- M6 nut – 4x
- M6 washer – 8x
- Exhaust springs – 4x
- Stainless steel silencer band K – 4x
- Rubber pad – 4x
- Finish Line TiPrep Anti-Seize – 1 packet
- M6 x 20mm allen bolt H – 4x

